



TECHNICAL DATA

Thermoflex T-CAP Adhesive

Cold Application Adhesive

DESCRIPTION

Thermoflex T-CAP Adhesive is a single component modified asphalt adhesive with a semi-liquid consistency for adhering SBS base and interply sheets or SBS capsheet membranes.

Each roof application has unique requirements and as such may require a specific system configuration and application. This product is manufactured to our product specification and our only obligation shall be to replace such product if proven to be defective. Thermo Manufacturing Systems, LLC does not assume responsibility for any defects in application of this product, or any deficiencies in any roof or substrates on which this product is applied, nor shall Thermo Manufacturing Systems, LLC be responsible or liable for injury, loss, or damage of any kind or character, direct or consequential, arising from the application, use or inability to use this product.

USES

Thermoflex T-CAP Adhesive can be used for bonding base, interply and capsheets to form a waterproof membrane. Thermoflex T-Cap Adhesive may be used to bond aggregate surfacing. DO NOT USE with Thermobond APP membranes. Thermoflex T-Cap Adhesive should be applied to the surface and allowed to flash for several minutes prior to installing either base, interply or capsheet membranes.

COLOR

Black

STORAGE STABILITY

One year when stored in unopened containers at 40°F - 80°F. DO NOT FREEZE.

CLEAN UP

Mineral spirits

LIMITATIONS

Thermoflex T-CAP Adhesive should not be shipped or stored at temperatures below 32°F. Thermoflex T-CAP Adhesive is not recommended for installations where ponding water is likely to occur for longer than 48 hours. Thermoflex T-CAP Adhesive should not be applied when weather conditions will not permit drying, i.e. high relative humidity (>90%), just before rain, dew, freezing temperatures or sunset.

PACKAGING

Available in 55 gallon drum

SURFACE PREPARATION

Thermoflex T-CAP Adhesive is supplied ready to use. Thinning is not required or recommended. If required, stir the materials slowly to ensure uniformity. DO NOT MIX AT HIGH SPEED. All surfaces to be coated must be clean, dry and free of any oil, grease or dirt.

APPLICATION INSTRUCTIONS

Apply with notched squeegee, or conventional or airless spray equipment

WARRANTY

When installed by an approved applicator and with an approved maintenance program, various extended warranties are available for specific Thermo Materials® Roof Restoration Systems by notifying Thermo Manufacturing Systems, LLC PRIOR to job start. Call for details regarding warranty application documentation requirements.

APPROVALS



©2014 Thermo Manufacturing Systems, LLC

P.O. Box 218

Lindale, TX 75771

(800) 882-7007

(903) 881-8771

FAX (903) 881-8787

The information contained herein is believed to be reliable. All recommendations or suggestions are made without guarantee in as much as conditions and methods of commercial use are beyond our control. Properties given are typical values and are not specifications unless otherwise stated.