



TECHNICAL DATA

Thermo Leak Locker

Repair Kit

DESCRIPTION

Thermo Leak Locker is equipped with high-quality roof repair and sealing products suitable for use on all common roof substrates. Thermo Leak Locker includes water-based and solvent-based mastics and sealants and the application tools to repair tough roofing problems in most any kind of weather.

PRODUCT

- 1 Gallon Wet-Seal
- 1 Gallon Thermolene® SEBS Mastic
- 1 Quart Thermolastic® Fibrated Mastic
- 2 Tubes Thermolastic® Acrylic Sealant
- 2 Tubes Thermolene® SEBS Sealant
- 1 Roll 6"x50' Thermopolyester SB-075
- 1 Roll 6"x25' Thermo Tape

- 1 Pair Sunglasses
- 1 Pair Scissors
- 1 Can Opener Wrench
- 2 Chip Brushes
- 2 Pair Rubber Gloves
- 2 Stir Sticks
- 1 Adhesive Spreader – Yellow
- 2 Plastic Putty Knives – Black
- 1 CD with Technical Data & MSD Information

USE

- Designed for use on wet or damp roof surfaces
- High performance, elastomeric, single component flashing compound
- Concentrated, fibrated acrylic sealant for roof seams, fasteners, bolts, and to patch and repair
- Gun-grade air-drying sealant with excellent adhesion to most surfaces
- High performance, elastomeric, single component, gun-grade sealant
- Stitchbonded polyester used in conjunction with mastic for reinforcing flashings and seams
- Flashing and seam tape designed for use on metal surfaces that conforms to virtually any shape

LIMITATIONS

Read Technical Data sheets for proper application instructions and limitations of each product. Thoroughly read MSDS and follow safety precautions.

SURFACE PREPARATION

All products in the Thermo Leak Locker are supplied ready to use. Thinning is not required or recommended. If required, stir the materials slowly to ensure uniformity. DO NOT MIX AT HIGH SPEED. All surfaces to be coated must be clean, dry and free of any oil, grease, dirt or rust. Rust must be removed and area treated with appropriate Thermo Materials® products.

©2014 Thermo Manufacturing Systems, LLC

P.O. Box 218

Lindale, TX 75771

(800) 882-7007

(903) 881-8771

FAX (903) 881-8787

The information contained herein is believed to be reliable. All recommendations or suggestions are made without guarantee in as much as conditions and methods of commercial use are beyond our control. Properties given are typical values and are not specifications unless otherwise stated.