



TECHNICAL DATA

Thermopoxy®

2-Part Epoxy Primer

DESCRIPTION

Thermopoxy® is a two-component epoxy polyamide primer for use on wood, concrete and metal surfaces prior to application of fluid-applied waterproofing systems.

Each roof application has unique requirements and as such may require a specific system configuration and application. This product is manufactured to our product specification and our only obligation shall be to replace such product if proven to be defective. Thermo Manufacturing Systems, LLC does not assume responsibility for any defects in application of this product, or any deficiencies in any roof or substrates on which this product is applied, nor shall Thermo Manufacturing Systems, LLC be responsible or liable for injury, loss, or damage of any kind or character, direct or consequential, arising from the application, use or inability to use this product.

COLOR

Part A – Yellow
Part B – Clear

STORAGE STABILITY

One year when stored in separate unopened containers at 40°F - 80°F. DO NOT FREEZE. To prevent container rupture due to very high temperature, keep away from heat and/or open flames.

CLEAN UP

Mineral Spirits

LIMITATIONS

Thermopoxy® is blended with other components before use. Any mixture of components will have hazards of all components. Read all warning labels for all products used. Follow all precautions.

PACKAGING

Available in set – Part A and Part B 5 gallon pail each

APPLICATION INSTRUCTIONS

Mix THOROUGHLY 1 to 1 (equal parts) by volume Thermopoxy® Part A and Thermopoxy® Part B. Apply without additional thinning. Mix and use exactly what is needed. Product **will not** store in a closed container for later use.

WARRANTY

When installed by an approved applicator and with an approved maintenance program, various extended warranties are available for specific Thermo Materials® Roof Restoration Systems by notifying Thermo Manufacturing Systems, LLC **PRIOR** to job start. Call for details regarding warranty application documentation requirements.

©2015 Thermo Manufacturing Systems, LLC

P.O. Box 218

Lindale, TX 75771

(800) 882-7007

(903) 881-8771

FAX (903) 881-8787

The information contained herein is believed to be reliable. All recommendations or suggestions are made without guarantee in as much as conditions and methods of commercial use are beyond our control. Properties given are typical values and are not specifications unless otherwise stated.