



# TECHNICAL DATA

## Thermolastic® Fibrated Mastic

### Acrylic Latex Fibrated Mastic

#### DESCRIPTION

Thermolastic® Fibrated Mastic is a highly concentrated water-based acrylic caulking sealant. Thermolastic® Fibrated Mastic is an integral component of many Thermolastic® Roofing Systems. It is water resistant and flexible after curing. Thermolastic® Fibrated Mastic is an air-drying sealant with excellent adhesion to most surfaces including wood, concrete, metal, modified bitumen, SPF and BUR.

*Each roof application has unique requirements and as such may require a specific system configuration and application. This product is manufactured to our product specification and our only obligation shall be to replace such product if proven to be defective. Thermo Manufacturing Systems, LLC does not assume responsibility for any defects in application of this product, or any deficiencies in any roof or substrates on which this product is applied, nor shall Thermo Manufacturing Systems, LLC be responsible or liable for injury, loss, or damage of any kind or character, direct or consequential, arising from the application, use or inability to use this product.*

#### USES

Thermolastic® Fibrated Mastic makes an excellent sealant for horizontal and vertical joints for metal roofing systems. Use it to seal bolt heads, fasteners, material, or to patch and repair on existing acrylic, fiberglass, metal, aluminum and most plastics. Thermolastic® Fibrated Mastic may be applied directly to a variety of substrates without the use of additional primer.

#### COLOR

White

#### STORAGE STABILITY

One year when stored in unopened containers at 40°F - 80°F. DO NOT FREEZE.

#### CLEAN UP

Water

#### PRIMER

On properly prepared surfaces, no priming is needed for application to plywood, most metal, BUR, modified bitumen or SPF.

#### CURE TIMES

Thermolastic® Fibrated Mastic will cure under most conditions in 24 - 48 hours. Colder weather and/or higher humidity will tend to retard curing whereas warmer weather and/or lower humidity will tend to accelerate curing.

#### LIMITATIONS

Thermolastic® Fibrated Mastic will freeze and should not be shipped or stored at temperatures below 32°F. Thermolastic® Fibrated Mastic is not recommended for installations where ponding water is likely to occur for longer than 48 hours. Thermolastic® Fibrated Mastic should not be applied when weather conditions will not permit drying, i.e. high relative humidity (>90%), just before rain, dew, freezing temperatures or sunset.

#### PACKAGING

Available in 5 gallon pails

#### SURFACE PREPARATION

Thermolastic® Fibrated Mastic is supplied ready to use. Thinning is not required or recommended. If required, stir the materials slowly to ensure uniformity. DO NOT MIX AT HIGH SPEED. All surfaces to be coated must be clean, dry and free of any oil, grease, dirt or rust. Rust must be removed and area treated with appropriate Thermo Materials® products.

## **APPLICATION INSTRUCTIONS**

Apply with brush or trowel in uniform application.

## **WARRANTY**

When installed by an approved applicator and with an approved maintenance program, various extended warranties are available for specific Thermo Materials® Roof Restoration Systems by notifying Thermo Manufacturing Systems, LLC **PRIOR** to job start. Call for details regarding warranty application documentation requirements.

**©2018 Thermo Manufacturing Systems, LLC**

P.O. Box 218

Lindale, TX 75771

(800) 882-7007

(903) 881-8771

FAX (903) 881-8787

The information contained herein is believed to be reliable. All recommendations or suggestions are made without guarantee in as much as conditions and methods of commercial use are beyond our control. Properties given are typical values and are not specifications unless otherwise stated.